



• Web browser • Java support • Web configuration

Specification	
Graphic display	4,3" TFT, 480 x 272 pixel, 16 M colours (16:9)
Input	Touchscreen resistiv, 1 button
Audio	Beeper
Memory	256 MB RAM, 512 MB Flash
Processor	32 Bit Cortex-A8 RISC CPU 600 MHz
Software	
Operating system	Linux - 2.6 web browser and VNC
Interface	
USB	1 x 2.0* Host, Typ A
Ethernet	1 x 10/100BASE-T, RJ45
Environment/mechanical values	
Supply voltage	24 V DC (18 V...30 V), 2 W...6 W
Housing	Aluminium anodized, polyester film
EMC examinations	EN 61000-6-2, EN 61000-6-4
IP Rating	Front IP54, Back IP20 acc. EN 60529
Mounting	Front panel mounting
Outside dimension in mm (W x H x D)	140 x 96 x 39
Cut-out dimension in mm (W x H)	130 x 88
Weight approx.	400 g
Operating temperature	0 °C...50 °C
Storage temperature	-20 °C...70 °C
Ordering number	
24721.0000	PTE404/elrest/Linux
Applications	
	in many industries such as plastics, medical- and automation technology

Illustrations, descriptions, dimensions and specifications correspond to the circumstances or intentions at the time of printing this brochure. Changes of any kind, especially those resulting from technological progress, economic performance or a similar will be without notice. The external interconnection of equipment will be on your own responsibility

*Remark: USB 2.0 High Speed only

elrest Automationssysteme GmbH • Leibnizstraße 10 • 73230 Kirchheim unter Teck • Tel.: +49 (0) 7021 92025-0

© 2017 • www.elrest.de • All rights reserved

